


# U-Profile

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
10 x	10 x	2,0	0,140 *	●
10 x	20 x	2,0	0,248 *	●
12 x	12 x	1,5	0,134 *	●
12 x	12 x	2,0	0,173 *	●
12 x	13 x	2,0	0,184 *	●
14 x	12 x	2,0	0,184 *	●
14 x	16 x	2,0	0,227 *	●
15 x	15 x	2,0	0,221	●
15 x	20 x	1,5	0,211 *	●
15 x	20 x	2,0	0,275 *	●
16 x	13 x	1,5	0,158 *	●
20 x	10 x	2,0	0,194 *	●
20 x	15 x	2,0	0,248	●
20 x	20 x	1,5	0,231 *	●
20 x	20 x	2,0	0,302	●
20 x	20 x	3,0	0,437	●
20 x	25 x	2,0	0,356	●
20 x	30 x	2,0	0,410	●
20 x	40 x	2,0	0,518	●
20 x	40 x	2,5	0,641	●
25 x	15 x	2,0	0,275	●
25 x	20 x	2,0	0,329	●
25 x	20 x	3,0	0,478 *	●
25 x	25 x	2,0	0,383	●
25 x	25 x	3,0	0,559	●
25 x	40 x	2,0	0,545 *	●
30 x	15 x	2,0	0,302	●
30 x	15 x	3,0	0,437 *	●
30 x	20 x	2,0	0,356	●
30 x	20 x	3,0	0,518 *	●
30 x	30 x	2,0	0,464	●
30 x	30 x	3,0	0,680	●
30 x	40 x	3,0	0,842	●
30 x	50 x	3,0	1,004 *	●
30 x	60 x	2,0	0,788 *	●
35 x	20 x	2,0	0,383	●
35 x	25 x	2,0	0,437 *	●
35 x	35 x	2,0	0,545 *	●
35 x	35 x	3,0	0,802	●
35 x	53,5 x	3,5	1,276 *	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage




# U-Profile

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/-2/-9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
40 x	15 x	2,0	0,356 *	●
40 x	20 x	2,0	0,410	●
40 x	20 x	2,5	0,506	●
40 x	20 x	3,0	0,599	●
40 x	25 x	2,0	0,464	●
40 x	25 x	3,0	0,680	●
40 x	25 x	4,0	0,886 *	●
40 x	30 x	2,0	0,518 *	●
40 x	30 x	3,0	0,761	●
40 x	40 x	2,0	0,626	●
40 x	40 x	2,5	0,776	●
40 x	40 x	3,0	0,923	●
40 x	40 x	4,0	1,210	●
40 x	40 x	5,0	1,485	●
40 x	50 x	2,0	0,734 *	●
40 x	60 x	4,0	1,642 *	●
40 x	65 x	2,0	0,896 *	●
45 x	25 x	3,0	0,721	●
45,5 x	12 x	2,5	0,435 *	●
50 x	15 x	2,0	0,410 *	●
50 x	20 x	2,0	0,464	●
50 x	20 x	3,0	0,680 *	●
50 x	25 x	2,0	0,518	●
50 x	25 x	2,5	0,641	●
50 x	30 x	2,0	0,572	●
50 x	30 x	3,0	0,842	●
50 x	30 x	4,0	1,102	●
50 x	40 x	3,0	1,004 *	●
50 x	40 x	4,0	1,318	●
50 x	50 x	2,0	0,788	●
50 x	50 x	3,0	1,166	●
50 x	50 x	4,0	1,534	●
50 x	50 x	5,0	1,890	●
55 x	45 x	2,0	0,761 *	●
55 x	50 x	2,0	0,815 *	●
60 x	20 x	2,0	0,518	●
60 x	25 x	2,5	0,709 *	●
60 x	25 x	3,0	0,842 *	●
60 x	30 x	3,0	0,923 *	●
60 x	40 x	2,5	0,911	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage



# U-Profil

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
60 x	40 x	3,0	1,085	●
60 x	40 x	4,0	1,426	●
60 x	40 x	5,0	1,755	●
60 x	50 x	2,0	0,842 *	●
60 x	50 x	2,5	1,046 *	●
60 x	50 x	3,0	1,247	●
60 x	60 x	3,0	1,409 *	●
60 x	60 x	4,0	1,858	●
60 x	60 x	5,0	2,259 *	●
65 x	25 x	2,5	0,743	●
65 x	55 x	2,5	1,148	●
70 x	35 x	3,0	1,085 *	●
70 x	40 x	3,0	1,166 *	●
70 x	40 x	4,0	1,534 *	●
80 x	20 x	2,0	0,626	●
80 x	30 x	3,0	1,085	●
80 x	40 x	3,0	1,247	●
80 x	40 x	4,0	1,642	●
80 x	40 x	5,0	2,025 *	●
80 x	40 x	6,0	2,398 *	●
80 x	45 x	3,0	1,328 *	●
80 x	45 x	6,0	2,560 *	●
80 x	50 x	3,0	1,409	●
80 x	50 x	5,0	2,295	●
80 x	60 x	5,0	2,565 *	●
80 x	80 x	4,0	2,506 *	●
86 x	40 x	3,0	1,296	●
90 x	20 x	2,5	0,844 *	●
90 x	40 x	3,0	1,328	●
90 x	50 x	3,0	1,490	●
90 x	50 x	5,0	2,430 *	●
100 x	20 x	2,0	0,734 *	●
100 x	40 x	3,0	1,409	●
100 x	50 x	3,0	1,571 *	●
100 x	50 x	5,0	2,565	●
100 x	50 x	10,0	4,860 *	●
100 x	70 x	6,0	3,694 *	●
106 x	40 x	3,0	1,458	●
110 x	40 x	3,0	1,490 *	●
120 x	20 x	2,5	1,046 *	●

